

# DECLARATION OF PERFORMANCE

SalzSCorner-CPR-2016/11/04-GB



## PRODUCT

**Product type** Slow heat release appliance  
**Type designation** Salzburg S Corner  
**Product identification** See product instruction manual  
**Intended area of use** Heating of rooms in residential buildings  
**Fuel** Wood

## MANUFACTURER

**Name** Nordpeis AS  
**Address** Gjellebekkstubben 11  
3420 Lierskogen, Norway

## CHECKS

**According to AVCP Standard** System 3  
EN 15250:2007  
**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625  
has checked declared performance and issued test report no. RRF-50 16 4409

## DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1	EN 15250:2007
Minimum distances to combustible material	30 mm rear 250 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O <sub>2</sub> Oxygen nitride NO <sub>x</sub> at 13% O <sub>2</sub> Organic Gaseous Carbon at 13% O <sub>2</sub> Particulate Matter at 13 O <sub>2</sub>	CO : < 1500 mg / m <sup>3</sup> NO <sub>x</sub> : < 200 mg / m <sup>3</sup> OGC : < 120 mg / m <sup>3</sup> PM : < 40 mg / m <sup>3</sup>	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Total thermal output	23,6 kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P = 2,1 kW	
Flue gas temperature at nominal output	t <sub>a</sub> = 171 °C	
Energy efficiency	η = 84 %	

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS